nflexon

PRODUCT DESCRIPTION

1U Universal Sliding Fiber Shelf – 19" rack mount, sliding fiber shelf that supports multimode and singlemode fiber optic cables, populated adapter plates, jumpers, and pigtails for telecom room applications. It comes preconfigured with fiber splice trays and three blanking plates.

FEATURES	
Certifications & Compliance	RoHS Reach
Packaging	One per Box
Color	Black
Applications	Data Center Premise Telecommunication Networks Data Networks Ethernet Fiber Channel

DESCRIPTION	PRODUCT ID
1U Universal Sliding Fiber Shelf	OP001UBK00P0

nflexon

MATERIAL SPECIFICATIONS

Fiber Shelf	Commercial Grade Cold Rolled Steel with Black Power Coated Finish
Splice Trays	PC, UL94V-0

SHELF PHYSICAL SPECIFICATIONS

Height	1.75 in (44.5 mm)
Width	19 in (482.6 mm)
Depth	8 in (203.2 mm)
Weight (Net + Package)	11.3 lb (5.1 kg) + 1 lb (0.45 kg)

ENVIRONMENTAL SPECIFICATIONS

Storage Temperature	-40 °F to 154 °F (-40 °C to 68 °C)
Installation Temperature	-40 °F to 158 °F (-40 °C to 70 °C)
Operation Temperature	14 °F to 140 °F (-10 °C to 60 °C)
Humidity	10 % to 90 % RH

PACKAGE CONTENTS

1U Universal Sliding Fiber Shelf	Includes 1 fiber shelf with splice trays, fiber splice sleeves, 3 snap-in blanking plates, and 4 cable grommets