

PRODUCT SPECIFICATIONS

24-Port Blank Patch Panel



PRODUCT DESCRIPTION

1U 24-port blank patch panels that fit in standard 19" racks, offered in straight, staggered, and angled configurations, with an easy to install rear cable tie bar.

FEATURES		DESCRIPTION	PRODUCT ID
Certifications & Compliance	RoHS Reach ISO 9001 ISO 14001	Blank Patch Panel, Straight, 24 port with Rear Cable Tie Bar	PPBNSTBK24P0
Packaging	Box	Blank Patch Panel, Staggered, 24 Port with Rear Cable Tie Bar	PPBNSGBK24P0
Options	Black	Blank Patch Panel, Angled, 24 port with Rear Cable Tie Bar	PPBNANBK24P0

Note: These panels are blank. Keystone jacks need to be ordered separately.

Product images shown are for illustration purposes only

PRODUCT SPECIFICATIONS

24-Port Blank Patch Panel



1U 24-PORT STRAIGHT and STAGGERED PATCH PANEL SPECIFICATIONS

Material	Patch Panel & Cable Tie Bar	Commercial Grade Cold Rolled Steel with Black Powder Coated Finish
Dimensions	Height Width Depth	1.73 in (44 mm) 19.04 in (482.50 mm) .40 in (10.10 mm) without cable tie bar
Cable Tie Bar Depth		4.25 in (107.90 mm)
Operating Temperature Range		+14 °F to +140 °F (-10 °C to +60 °C)
Storage Temperature Range		-40 °F to +154 °F (-40 °C to +68 °C)
Humidity		10 % to 90 % RH
Color		Black
Package Contents	Patch Panel (with attached ground strap) Cable Tie Bar 8 Cable Ties Instructions	

1U 24-PORT ANGLED PATCH PANEL SPECIFICATIONS

Material	Patch Panel & Cable & Tie Bar Plastic Frame	Commercial Grade Cold Rolled Steel with Black Powder Coated Finish ABS, UL94V-0
Dimensions	Height Width Depth Front Protrusion	1.73 in (44 mm) 19.04 in (482.50 mm) .40 in (10.10 mm) without cable tie bar 3.60 in (91.40 mm)
Cable Manager Depth		4.25 in (107.90 mm)
Operating Temperature Range		+14 °F to +140 °F (-10 °C to +60 °C)
Storage Temperature Range		-40 °F to +154 °F (-40 °C to +68 °C)
Humidity		10 % to 90 % RH
Color		Black
Package Contents	Patch Panel Front Cap Cable Tie Bar 8 Cable Ties Instructions	