



PRODUCT DESCRIPTION

Patch cord organizers that include a 1U patch cord organizer, a 2U patch cord organizer, and a patch cord routing hanger.

FEATURES	
Certifications & Compliance	RoHS Reach ISO 9001 ISO 14001
Packaging Patch Cord Organizers Patch Cord Routing Hanger	Box Poly Bag
Options	1U 2U

DESCRIPTION	PRODUCT ID
Patch Cord Organizer, 1U	CM001UBK0010
Patch Cord Organizer, 2U	CM002UBK0010
Patch Cord Routing Hanger	CMFACCBK0010

Product Images Shown Are For Illustration Purposes Only

1U & 2U PATCH CORD ORGANIZER SPECIFICATIONS

Material	Panel Plastic "C" Hanger	Commercial Grade Cold Rolled Steel with Black Power Coated Finish ABS, UL94V-0	
Dimensions	Height Width Depth "C" Hanger Protrusion from Front of Panel	1U	2U
		1.73 in (44 mm) 19 in (482.60 mm) 0.06 in (1.60 mm) ~ 3.91 in (~ 99 mm)	3.46 in (88 mm) 19 in (482.60 mm) 0.06 in (1.60 mm) ~ 3.91 in (~ 99 mm)
Operating Temperature Range	+14 °F to +140 °F (-10 °C to +60 °C)		
Storage Temperature Range	-40 °F to +154 °F (-40 °C to +68 °C)		
Humidity	10 % to 90 % RH		
Color	Black		
Package Contents	Patch Cord Organizer with four attached "C" clips		

PATCH CORD ROUTING HANGER SPECIFICATIONS

Material	PC, UL94V-0		
Dimensions	Height	1.73 in (44 mm)	
	Width	0.73 in (18.5 mm)	
	Depth	3.03 in (77 mm)	
Operating Temperature Range	+14 °F to +140 °F (-10 °C to +60 °C)		
Storage Temperature Range	-40 °F to +154 °F (-40 °C to +68 °C)		
Humidity	10 % to 90 % RH		
Color	Black		
Package Contents	Patch Cord Routing Hanger		