



PRODUCT DESCRIPTION

Populated Adapter Plate – SC Simplex Singlemode adapters preloaded on a 6-port or a 12-port adapter plate. They are designed with a snap-in feature for easy installation.

FEATURES					
Certifications & Compliance	ANSI/TIA-568-C.3 ISO/IEC 11801 RoHS Reach ISO 9001 ISO 14001				
Packaging	Four per Box				
Color	<table border="0"> <tr> <td>Populated Adapter Plate</td> <td>Black</td> </tr> <tr> <td>SC Simplex Singlemode Adapter</td> <td>Blue</td> </tr> </table>	Populated Adapter Plate	Black	SC Simplex Singlemode Adapter	Blue
Populated Adapter Plate	Black				
SC Simplex Singlemode Adapter	Blue				
Applications	Data Center Premise Telecommunication Networks Data Networks Ethernet Fiber Channel				
Options	6 SC Simplex Singlemode Adapters 12 SC Simplex Singlemode Adapters				

DESCRIPTION	PRODUCT ID
6-Port Adapter Plate with SC Simplex SM Adapters	OP1SCSBL06P0
12-Port Adapter Plate with SC Simplex SM Adapters	OP1SCSBL12P0

PRODUCT SPECIFICATIONS
SC Simplex Singlemode Adapter Plates



MATERIAL SPECIFICATIONS

Adapter Plate	Commercial Grade Cold Rolled Steel with Black Power Coated Finish
SC Simplex Singlemode Adapter	Thermoplastic Polymer

ADAPTER PLATE PHYSICAL SPECIFICATIONS

	6-Port Adapter Plate	12-Port Adapter Plate
Height	1.5 in (38.0 mm)	
Width	3.88 in (98.5 mm)	
Depth (with SC Adapter)	1.39 in (35.28 mm) / 1.32 in (33.64 mm)	
Weight (Net x 4 + Package)	8.5 oz (241.5 g) + 3 oz (85.0 g)	9.3 oz (263.7 g) + 3 oz (85.0 g)

ENVIRONMENTAL SPECIFICATIONS

Storage Temperature	-40 °F to 154 °F (-40 °C to 68 °C)
Installation Temperature	-40 °F to 158 °F (-40 °C to 70 °C)
Operation Temperature	14 °F to 140 °F (-10 °C to 60 °C)
Humidity	10 % to 90 % RH

PACKAGE CONTENTS

Populated Adapter plates	Includes 4 populated SC Singlemode adapter plates
--------------------------	---